STATE OF MISSOURI

DEPARTMENT OF NATURAL RESOURCES

MISSOURI CLEAN WATER COMMISSION



MISSOURI STATE OPERATING PERMIT

In compliance with the Missouri Clean Water Law, (Chapter 644 R.S. Mo. as amended, hereinafter, the Law), and the Federal Water Pollution Control Act (Public Law 92-500, 92nd Congress) as amended,

Permit No. MO-0093319

Owner: Stream Line Properties, LLC

Address: 862 South Outer Road, St. Clair, MO 63077

Continuing Authority: Same as above Address: Same as above

Facility Name: Stream Line MHP (formerly Bill's Trailer Park)
Address: 1608 East Springfield Road, Sullivan, MO 63080

Legal Description: SE ¼, SW ¼, Sec. 34, T41N, RE2, Franklin County

Receiving Stream: Unnamed Tributary to Winsel Creek (U)

First Classified Stream and ID: Spring Creek (C)(02072) USGS Basin & Sub-watershed No.: (07140103-090007)

is authorized to discharge from the facility described herein, in accordance with the effluent limitations and monitoring requirements as set forth herein:

FACILITY DESCRIPTION

See page 2

This permit authorizes only wastewater discharges under the Missouri Clean Water Law and the National Pollutant Discharge Elimination System; it does not apply to other regulated areas. This permit may be appealed in accordance with Section 644.051.6 of the Law.

February 20, 2004 March 24, 2006

Effective Date Revision Date Doyle Childers, Director, Department of Natural Resources Executive Secretary, Clean Water Commission

February 19, 2009

Expiration Date MO 780-0041 (10-93)

Mike Struckhoff., Director, St. Louis Regional Office

FACILITY DESCRIPTION (continued)

Outfall #001 - Mobile Home Park - SIC #4952 (Closed)

Three cell lagoon/sludge is retained in lagoon.

Design population equivalent is 125.

Design flow is 10,125 gallons per day.

Design sludge production is 2.025 dry tons/year.

Legal Description: NE ¼, SE ¼, SW ¼, Sec. 34, T41N, R2E, Franklin County

Outfall #002 - Mobile Home Park - SIC #4952 (Closed)

Three cell lagoon/sludge is retained in lagoon.

Design population equivalent is 81.

Design flow is 6,075 gallons per day.

Design sludge production is 1.215 dry tons/year.

Legal Description: SW ¼, SE ¼, SW ¼, Sec. 34, T41N, R2E, Franklin County

Outfall #003 - Mobile Home Park – SIC #4952 (New facility)

Septic tank/recirculating sand filter/chlorination (dechlorination to be provided under schedule of compliance).

Design population equivalent is 154.

Design flow is 15,400 gallons per day.

Design sludge production is 1.0 dry tons/year.

Legal Description: NE ¼, SE ¼, SW ¼, Sec. 34, T41N, R2E, Franklin County

A. INTERIM EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

PAGE NUMBER 3 of 5

PERMIT NUMBER MO-0093319

The permittee is authorized to discharge from outfall(s) with serial number(s) as specified in the application for this permit. The final effluent limitations shall become effective upon issuance and remain in effect until December 31, 2006. Such discharges shall be controlled, limited and monitored by the permittee as specified below:

(OUTFALL NUMBER AND EFFLUENT		INTERIM EFFLUENT			MONITORING REQUIREMENTS	
PARAMETERS)	UNITS	DAILY MAXIMUM	WEEKLY AVERAGE	MONTHLY AVERAGE	MEASUREMENT FREQUENCY	SAMPLE TYPE
Outfall #003						
Flow	MGD	*		*	Once/month***	24 hr. estimate
Biochemical Oxygen Demand ₅ **	mg/L		15	10	Once/quarter***	Grab
Total Suspended Solids**	mg/L		20	15	Once/quarter***	Grab
Fecal Coliform	#/100mL	1000		400	Once/quarter***	Grab
Total Residual Chlorine	mg/L	1.0		1.0	Once/quarter***	Grab
pH – Units	SU	**		**	Once/quarter***	Grab

MONITORING REPORTS SHALL BE SUBMITTED QUARTERLY; THE FIRST REPORT IS DUE <u>July 28, 2006</u>. THERE SHALL BE NO DISCHARGE OF FLOATING SOLIDS OR VISIBLE FOAM IN OTHER THAN TRACE AMOUNTS.

B. STANDARD CONDITIONS

IN ADDITION TO SPECIFIED CONDITIONS STATED HEREIN, THIS PERMIT IS SUBJECT TO THE ATTACHED Parts I & III STANDARD CONDITIONS DATED October 1, 1980 and August 15, 1994, AND HEREBY INCORPORATED AS THOUGH FULLY SET FORTH HEREIN.

MO 780-0010 (8/91)

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS (continued)

- * Monitoring requirement only.
- ** pH is measured in pH units and is not to be averaged. The pH is limited to the range of 6.0-9.0 pH units.
- *** Sample once per quarter in the months of March, June, September & December.

PAGE NUMBER 4 of 5

A. FINAL EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

PERMIT NUMBER MO-0093319

The permittee is authorized to discharge from outfall(s) with serial number(s) as specified in the application for this permit. The final effluent limitations shall become effective January 1, 2007 and remain in effect until expiration of the permit. Such discharges shall be controlled, limited and monitored by the permittee as specified below:

	(OUTFALL NUMBER AND EFFLUENT PARAMETERS)		FINAL EF	FLUENT LIM	ITATIONS	MONITORING REQUIREMENTS	
		UNITS	DAILY MAXIMUM	WEEKLY AVERAGE	MONTHLY AVERAGE	MEASUREMENT FREQUENCY	SAMPLE TYPE
	Outfall #003						
	Flow	MGD	*		*	Once/month***	24 hr. estimate
	Biochemical Oxygen Demand₅**	mg/L		15	10	Once/quarter***	Grab
	Total Suspended Solids**	mg/L		20	15	Once/quarter***	Grab
	Fecal Coliform	#/100mL	1000		400	Once/quarter***	Grab
	Total Residual Chlorine (See note 1)	mg/L	0.019		0.010	Once/quarter***	Grab
	pH – Units	SU	**		**	Once/quarter***	Grab

MONITORING REPORTS SHALL BE SUBMITTED QUARTERLY; THE FIRST REPORT IS DUE <u>APRIL 28, 2007</u>. THERE SHALL BE NO DISCHARGE OF FLOATING SOLIDS OR VISIBLE FOAM IN OTHER THAN TRACE AMOUNTS.

B. STANDARD CONDITIONS

IN ADDITION TO SPECIFIED CONDITIONS STATED HEREIN, THIS PERMIT IS SUBJECT TO THE ATTACHED Parts I & III STANDARD CONDITIONS DATED October 1, 1980 and August 15, 1994, AND HEREBY INCORPORATED AS THOUGH FULLY SET FORTH HEREIN.

MO 780-0010 (8/91)

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS (continued)

- * Monitoring requirement only.
- ** pH is measured in pH units and is not to be averaged. The pH is limited to the range of 6.0-9.0 pH units.
- *** Sample once per quarter in the months of March, June, September & December.

Note 1 - This permit contains a Total Residual Chlorine (TRC) limit.

a. This effluent limit is below the minimum quantification level (ML) of the most common and practical EPA approved CLTRC methods. The department has determined the current acceptable ML for total residual chlorine to be 0.13 mg/L when using the DPD Colorimetric Method #4500-CL G. from Standard Methods for the Examination of Water and Wastewater. The permittee will conduct analyses in accordance with this method, or equivalent, and report actual analytical values. Measured values greater than or equal to the minimum quantification level of 0.13 mg/L will be considered violations of the permit and values less than the minimum quantification level of 0.13 mg/L will be considered to be in compliance with the permit limitation. The minimum quantification level does not authorize the discharge of chlorine in excess of the effluent limits stated in the permit.

C. SPECIAL CONDITIONS

- 1. This permit may be reopened and modified, or alternatively revoked and reissued, to:
 - a. Comply with any applicable effluent standard or limitation issued or approved under Sections 301(b)(2)(C) and (D), 304(b)(2), and 307(a) (2) of the Clean Water Act, if the effluent standard or limitation so issued or approved:
 - (1) contains different conditions or is otherwise more stringent than any effluent limitation in the permit; or
 - (2) controls any pollutant not limited in the permit.
 - b. Incorporate new or modified effluent limitations or other conditions, if the result of a waste load allocation study, toxicity test or other information indicates changes are necessary to assure compliance with Missouri's Water Quality Standards.
 - c. Incorporate new or modified effluent limitations or other conditions if, as the result of a watershed analysis, a Total Maximum Daily Load (TMDL) limitation is developed for the receiving waters which are currently included in Missouri's list of waters of the state not fully achieving the state's water quality standards, also called the 303(d) list.

The permit as modified or reissued under this paragraph shall also contain any other requirements of the Clean Water Act then applicable.

- 2. All outfalls must be clearly marked in the field.
- 3. Permittee will cease discharge by connection to areawide wastewater treatment system within 90 days of notice of its availability.
- 4. Changes in Discharges of Toxic Substances.

The permittee shall notify the Director as soon as it knows or has reason to believe:

- a. That any activity has occurred or will occur which would result in the discharge of any toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following "notification levels:"
 - (1) One hundred micrograms per liter (100 µg/L);
 - (2) Two hundred micrograms per liter (200 µg/L) for acrolein and acrylonitrile; five hundred micrograms per liter (500 µg/L) for 2,5 dinitrophenol and for 2-methyl-4, 6-dinitrophenol; and one milligram per liter (1 mg/L) for antimony;
 - (3) Five (5) times the maximum concentration value reported for the pollutant in the permit application;
 - (4) The level established in Part A of the permit by the Director.
- b. That they have begun or expect to begin to use or manufacture as an intermediate or final product or byproduct any toxic pollutant, which was not reported in the permit application.
- c. That the effluent limit established in part A of the permit will be exceeded.
- 5. Report as no-discharge when a discharge does not occur during the report period.

6. Water Quality Standards.

- a. Discharges to waters of the state shall not cause a violation of water quality standards rule under 10 CSR 20-7.031, including both specific and general criteria.
- b. General Criteria. The following general water quality criteria shall be applicable to all waters of the state at all times including mixing zones. No water contaminant, by itself or in combination with other substances, shall prevent the waters of the state from meeting the following conditions:
 - (1) Waters shall be free from substances in sufficient amounts to cause the formation of putrescent, unsightly or harmful bottom deposits or prevent full maintenance of beneficial uses;
 - (2) Waters shall be free from oil, scum and floating debris in sufficient amounts to be unsightly or prevent full maintenance of beneficial uses;
 - (3) Waters shall be free from substances in sufficient amounts to cause unsightly color or turbidity, offensive odor or prevent full maintenance of beneficial uses;
 - (4) Waters shall be free from substances or conditions in sufficient amounts to result in toxicity to human, animal or aquatic life;
 - (5) There shall be no significant human health hazard from incidental contact with the water;
 - (6) There shall be no acute toxicity to livestock or wildlife watering;
 - (7) Waters shall be free from physical, chemical or hydrologic changes that would impair the natural biological community;
 - (8) Waters shall be free from used tires, car bodies, appliances, demolition debris, used vehicles or equipment and solid waste as defined in Missouri's Solid Waste Law, section 260.200, RSMo, except as the use of such materials is specifically permitted pursuant to section 260.200-260.247.

- 7. Sludge and Biosolids Use For Domestic Wastewater Treatment Facilities
 - a. Permittee shall comply with the pollutant limitations, monitoring, reporting, and other requirements in accordance with the attached permit Standard Conditions.
 - b. If sludge is not removed by a contract hauler, permittee is authorized to land apply biosolids. Permit Standard Conditions, Part III shall apply to the land application of biosolids. Permittee shall notify the department at least 180 days prior to the planned removal of biosolids. The department may require submittal of a biosolids management plan for department review and approval as determined appropriate on a case-by-case basis.

C. SCHEDULE OF COMPLIANCE

The permittee shall install dechlorination equipment to enable the facility to achieve compliance with the final effluent limitations by December 31, 2006.